

November 19<sup>th</sup> 2015

Addendum to RFP SMGMN-0102 Motorized Cleaning Machines

This addendum modifies Schedule 4 in the original documents dated November 9<sup>th</sup> 2015.

## **SCHEDULE 4**

### **TECHNICAL SPECIFICATIONS**

---

#### **ALL BIDS TO INCLUDE;**

- Optional 3 year service agreement for any machines that require regular scheduled maintenance from a qualified technician
- Delivery lead time
- Full training on all machines submitted based on recommendations of the manufacturer, to be performed at the Stadium

#### **RIDING SCRUBBER LARGE (Tennant T20 or equivalent)**

Ride on scrubber must meet the following minimum requirements

- 54 inch wide cleaning path with side scrub assemble
- 450rpm cylindrical brushes
- 375 lb cylindrical brush down pressure
- 80 gallon solution tank
- 95 gallon recovery tank
- Speed variable up to 8mph forward, 4 mph reverse
- LPG/Gas
- With Soap-less Cleaning Technology – Electrically Activated Water Technology for chemical free cleaning

#### **RIDING SCRUBBER Small (Tennant T12 or equivalent)**

Ride on scrubber must meet the following minimum requirements

- 40 inch wide cleaning path with side scrub assemble
- 325rpm cylindrical brushes
- 250 lb cylindrical brush down pressure
- 35 gallon solution tank



- 40 gallon recovery tank
- Speed variable up to 5mph forward, 2.5 mph reverse
- High Capacity Rechargeable battery system with minimum of 4 hours usage on full charge
- With Soap-less Cleaning Technology - Electrically Activated Water Technology for chemical free cleaning

### **RIDING SWEEPER SMALL (Tennant S20 or equivalent)**

Ride on sweeper must meet the following minimum requirements

- 60" wide dump
- 62 inch wide cleaning path with dual side brush
- 11 cu ft debris hopper
- 80 sq ft canister dust filter
- Speed variable up to 5mph forward, 2.5 mph reverse
- Price all fuel options, high capacity long life for electric power.

### **WALK BEHIND SCRUBBER (Tennant 5680 or equivalent)**

Walk behind scrubber must meet the following minimum requirements

- 32 inch wide cleaning path
- 200 rpm disc brushes
- 200 lb maximum disc down pressure
- 30 gallon solution tank
- 40 gallon recovery tank
- Rechargeable battery system with minimum of 3 hrs usage on full charge
- Optional off aisle scrub wand attachment
- With Soap-less Cleaning Technology - Electrically Activated Water Technology for chemical free cleaning

### **WALK BEHIND SCRUBBER Small (Tennant T1, T1 Lithium or equivalent)**

Walk behind scrubber must meet the following minimum requirements

- 15 inch wide cleaning path
- 2400 rpm cylindrical corded disc brushes
- 33 lb disc down pressure
- 3 gallon solution tank



- 4.5 gallon recovery tank
- 50ft corded electrical

### **WIDE AREA CARPET EXTRACTOR (Tennant R14 or equivalent)**

Ride on carpet extractor must meet the following minimum requirements

- 28 inch wide cleaning path
- Capable of 13000 sq ft extraction per hour
- 30 gallon solution tank
- 30 gallon recovery tank
- Deep extraction technology
- Low moisture technology (Ready Space or equivalent)
- Rechargeable battery system with minimum of 3 hrs usage on full charge

### **CARPET EXTRACTOR (Tennant 1020 or equivalent)**

Carpet extractor must meet the following minimum requirements

- 20 inch wide cleaning path
- 14.5 gallon solution tank
- 50ft safety detachable yellow cord
- Optional wand and hose attachment

### **SPOT EXTRACTOR (Tennant EX Spot 2 or equivalent)**

Ride on carpet extractor must meet the following minimum requirements

- 4 inch wide cleaning path, with 8' hoses
- 1.5 gallon solution tank
- 25ft safety yellow cord

### **DUAL MOTOR UPRIGHT VACUUM (Tennant V-DMU-14 or equivalent)**

Upright vacuum must meet the following minimum requirements

- 1200W vacuum motor and separate brush motor
- HEPA 5 filtration
- On board tool kit
- Cord strain relief
- 50' cord
- Provide spare filters, belts and brushes.

### **CARPET BLOWER (Tennant Blower or equivalent)**

Carpet blower must meet the following minimum requirements

- 2500 cfm of airflow
- 3 speed settings
- 115V with 20ft safety yellow cord
- Stackable units
- Multiple position settings

**WIDE AREA VACUUM (Tennant V-WA-26 or equivalent)**

Upright vacuum must meet the following minimum requirements

- 26” cleaning path
- Dual motor system
- HEPA 5 filtration
- Cord strain relief
- 50’ cord
- Provide spare filters, belts and brushes.

**WIDE AREA VACUUM (Tennant V-WA-30 or equivalent)**

Upright vacuum must meet the following minimum requirements

- 30” cleaning path
- Dual motor system
- HEPA 5 filtration
- Cord strain relief
- 50’ cord
- Provide spare filters, belts and brushes.